

Page: 1 / 6

1. Identification of the Substance / Preparation and Company:

Commercial product name:	HinriDon liquid
Use / Purpose	Denture Base Resin, hot-curing acrylic, liquid component of the
	2-component acrylic system based on methyl methacrylate
	(powder and liquid), for the purpose of crafting individual
	dentures.
Company / Manufacturer:	ERNST HINRICHS GmbH
	Borsigstr. 1
	D - 38644 Goslar
	0 53 21 / 5 06 24
	0 53 21 / 5 08 81
	info@hinrichs-dental.de / www.hinrichs-dental.de

2. Hazards Identification:

Hazard symbols





Highly flammable

Irritating

Special guidelines concerning dangers to humans ad the environment:

Highly flammable. Irritating to respiratory system and skin. May cause sensitization by skin contact.

3. Composition / Information on Ingredients:

Chemical characterization:

Mixture on the basis of methyl methacrylate.

	Hazardous ingredients: Concentration: Chemical formula: CAS Number EINECS Number Index Number Hazard symbols: R-phrases	Methyl methacrylate 60 to 100 % C_5 H ₈ O ₂ $80-62-6$ $201-297-1$ $607-035-00-6$ F, Xi $11-37/38-43$
4.	First aid measures:	
4.1	General Information	Remove soiled, soaked clothing immediately. Medical treatment is necessary if symptoms occur that are obviously caused by skin or eye contact with the product or by inhalation of its vapours.
4.2	After inhalation:	In case of inhalation remove casualty to fresh air and allow to rest. Seek medical advice.
4.3	After contact with the skin:	In case of contact with skin wash off immediately with soap and water. If skin irritation occurs, seek medical advice.
4.4	After contact with the eyes:	In case of contact with the eyes rinse thoroughly with plenty of water while keeping the eyelids open. If irritation persists seek medical advice.
4.5	After swallowing:	Do not induce vomiting. Seek medical advice immediately.

reviewed on: 01.08.2009



5. 5.1	Fire Fighting measures:	
	Suitable extinguishing media:	Foam, dry powder, carbon dioxide
5.2	Unsuitable extinguishing media for	Water
	safety reasons:	
5.3	Special protective equipment for fire	Wear self-contained breathing apparatus.
	fighting:	
6.	Accidental release measures:	
6.1	Personal precautionary measures:	Assure appropriate air-flow. Wear protective clothing. Keep away
		from ignition sources. Use breathing apparatus if exposed to
~ ~		vapours/dust/mist/aerosol.
6.2 6.3	Environmental protection measures: Measures for cleaning:	Do not discharge into drains / surface water / groundwater.
	Large quantities:	Remove mechanically (hydraulic pump). Assure explosion-safe
	3. 1	measures.
	Smaller quantities:	Pick up with liquid absorbing material (sand, diatomaceous
		earth, acid absorbent, sawdust or tissues). Dispose of in
		accordance with regulations.
7. 7.1	Handling and Storage:	
	Instructions on safe handling:	Keep container well closed. Assure appropriate air-flow.
7.2	Information on fire and explosion	Keep away from ignition sources – No smoking. Take
	protection:	precautionary measures against static discharges. In the event
		of fire, cool the endangered containers with water. When heated
		above the flash point and/or during spraying (atomizing),
		ignitable mixtures may form in the air. Use explosion-proof equipment only.
7.3	Storage:	
	Requirements for storage areas and	Keep only the original container at a temperature not exceeding
	containers:	25°C. Protect from light. Fill the container by approx. 90 % only
		as oxygen (air) is required for stabilization. With large storage
		containers make sure the oxygen (air) supply is sufficient to
		ensure stability.
7.4	Additional Information:	If the liquid should cool down to a temperature of lower than
		10°C some of the ingredients may crystallize and sink to the
		bottom. If the materials temperature rises up to room
		temperature again these crystals dissolve again. The properties
		of the material will not be affected by this phenomena.
8.	Exposure controls / Personal protection:	
8.1		sition according to point 10, with limit values related to the place of
	work which requires monitoring.	
	Methyl methacrylate	80-62-6
	OES (long-term) 2003	208 mg/m ³ – 50 ppm
	OES (short term) 2003	416 mg/m ³ – 100 ppm
8.2	Personal protective equipment :	
	General protective measures:	Do not inhale vapours. Avoid contact with eyes and skin.
	Respiratory protection:	Breathing apparatus in case of high concentrations, short term:
		filter appliance filter A

Breathing apparatus in case of high concentrations, short term: filter appliance, filter A.

MATERIAL SAFETY DATA SHEET

According to (EG) 1907/2006 (REACH) ERNST HINRICHS GmbH

Date of printing: 26.01.2012

HinriDon liquid



Page: 3 / 6

Hand protection:	Wear protective gloves made of butyl rubber (0,7 mm), break through time 300 min (EN 374). In practice, due to variable exposure conditions, this information can only be an aid to orientation for the selection of a suitable chemical protection glove. In particular, this information does not substitute suitability tests by the user.
Eye protection:	Tightly fitting goggles.
Body protection:	When handling larger quantities wear face shield, apron and chemical resistant boots.
Hygiene measures:	Store work clothing separately. Remove soiled or soaked clothing immediately. Follow the usual good standards of occupational hygiene. Clean skin clearly after work; apply skin cream.
General information:	Gloves should be changed regularly, especially after over excessive contact with the product. A different type of glove should be considered for each workspace.

9. Physical and chemical properties:

Appearance	
Form:	Liquid
Colour:	Colourless
Odour:	Ester-like
Changes in physical state	
Melting point:	-48,2 °C
Boiling point:	100,3 °C (at 1.013 hPa)
Flashpoint:	10 °C (DIN 51755)
Ignition temperature:	430 °C (DIN 51794)
lower explosion limit:	2,1 % (V)
Upper explosion limit:	12,5 % (V)
Vapour pressure:	38,7 hPa (at 20 °C)
Density	0,94 g/cm ³ (at 20 °C)
Bulk density:	> 1 (at 20 °C)
Solubility in water:	15,9 g/l (at 20 °C)
Qualitative:	miscible with most organic solvents
pH-value:	not applicable
n-Octanol/water partition coefficient:	log pow 1,38 (measured)
Dynamic viscosity:	0,63 mPa.s (at 20 °C, Brookfield)
Further information:	none

10. Stability and Reactivity:

Thermal decomposition:	No decomposition when used as directed.
Hazardous reactions:	Polymerisation with heat evolution may occur in the presence of
	radical forming substances (e.g. peroxides), reducing
	substances, and/or heavy metal ions.
Hazardous decomposition products:	None when used as directed.

11. Toxicological Information:

The following information is related to the component methyl methacrylate

Acute oral toxicity:	> 5.000 mg/kg; practically non-toxic if swallowed; LD50 rat, OECD 401
Acute inhalational toxicity:	29,8mg/l; low toxicity by inhalation; LC50 rat, exposure 4h
Acute dermal toxicity:	> 5.000 mg/kg; practically non-toxic in contact with skin; LD50 rabbit
Irritant effect on skin:	not irritating; rabbit exposure 24h; FDA 1959 Draize, occlusive

MATERIAL SAFETY DATA SHEET

According to (EG) 1907/2006 (REACH) ERNST HINRICHS GmbH

Date of printing: 26.01.2012

HinriDon liquid



Page: 4 / 6

	Irritant effect on eyes: Sensitization:	not irritating; rabbit; Draize In sensitization tests on guinea pigs with and without adjuvant, both positive and negative results were found. In humans various types of allergic reactions have been observed (symptoms: headache, eye irritations, skin affections).
	Toxicity on repeated administration:	NOAEL 25ppm; at said doses no adverse effects were observed. At higher doses adverse effects were observed; rat; inhalative 2 a, 25-400ppm (Findings: damage to mucous membranes in the nose at 400ppm). NOAEL 2000ppm; rat; drinking water 2 a, 6-20ppm (Findings: no
	Mutagenicity:	toxic effects) Positive as well as negative results within in vitro mutagenicity / genotoxicity testes. No experimental indication of genotoxicity in vivo available. In summary not mutagenic according to internationally accepted criteria.
	Carcinogenicity:	Non-carcinogenic in inhalation and feeding studies carried out on
	Reprotoxycity / teratogenicity:	rats, mice, dogs. No indications of toxic effects were observed in reproduction studies in animals.
	Additional information:	Avoid contact with skin and eyes and inhalation of the product vapours.
12.	Ecological Information:	Information on elimination (persistence degradability)
	Biodegradability:	readily degradable, ca. 94 %
	Ecotoxicological effect	Method: OECD 301 C, 14 d
	Ecotoxicological effect	
	Ecotoxicological effect Fishtoxicity (LC50)	> 79 mg/l
	Fishtoxicity (LC50)	> 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h
		> 79 mg/l
	Fishtoxicity (LC50)	> 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l
	Fishtoxicity (LC50) Daphnia toxicity (EC50) NOEC	> 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l Daphnia magma, OECD 202, 21 d
	Fishtoxicity (LC50) Daphnia toxicity (EC50)	> 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l Daphnia magma, OECD 202, 21 d 37 mg/l
	Fishtoxicity (LC50) Daphnia toxicity (EC50) NOEC Algae toxicity (EC3)	 > 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l Daphnia magma, OECD 202, 21 d 37 mg/l Scenedesmus quadricauda, DIN 38412 section 9, 8 d
	Fishtoxicity (LC50) Daphnia toxicity (EC50) NOEC	 > 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l Daphnia magma, OECD 202, 21 d 37 mg/l Scenedesmus quadricauda, DIN 38412 section 9, 8 d 170 mg/l
	Fishtoxicity (LC50) Daphnia toxicity (EC50) NOEC Algae toxicity (EC3) Algae toxicity (EC50)	 > 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l Daphnia magma, OECD 202, 21 d 37 mg/l Scenedesmus quadricauda, DIN 38412 section 9, 8 d 170 mg/l Selenastrum capricornutum, OECD 201, 96h
	Fishtoxicity (LC50) Daphnia toxicity (EC50) NOEC Algae toxicity (EC3)	 > 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l Daphnia magma, OECD 202, 21 d 37 mg/l Scenedesmus quadricauda, DIN 38412 section 9, 8 d 170 mg/l
13	Fishtoxicity (LC50) Daphnia toxicity (EC50) NOEC Algae toxicity (EC3) Algae toxicity (EC50) Bakteria toxicity (EC0) Additional ecological Information:	 > 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l Daphnia magma, OECD 202, 21 d 37 mg/l Scenedesmus quadricauda, DIN 38412 section 9, 8 d 170 mg/l Selenastrum capricornutum, OECD 201, 96h 100 mg/l Pseudomonas putida
<u>13.</u> 13.1	Fishtoxicity (LC50) Daphnia toxicity (EC50) NOEC Algae toxicity (EC3) Algae toxicity (EC50) Bakteria toxicity (EC0)	 > 79 mg/l Oncorhynchus mykiss, rainbow trout, OECD 203 GLP, 96 h 69 mg/l Daphnia magma, OECD 202, 48h 37 mg/l Daphnia magma, OECD 202, 21 d 37 mg/l Scenedesmus quadricauda, DIN 38412 section 9, 8 d 170 mg/l Selenastrum capricornutum, OECD 201, 96h 100 mg/l Pseudomonas putida



Page: 5 / 6

13.3 Code of waste EWC

07 02 08

Waste from the manufacture, formulation, supply and use (MFSU) of plastics, synthetic rubber and man-made fibres – or still bottoms and reaction residues. Always check the given waste codes according to the actual conditions of manufacturing, formulation or use in your facilities.

14. Transport information:

14.	Transport information:	
	Overland Transport ADR/RID/GGVSE	
	Class: Dangerous cargo number: UN Number:	3 flammable liquids 339 1247
	Packaging group: Label:	 3
	Declaration of the good:	UN 1247 METHYL METHACRYLATE, MONOMER, STABILIZED, 3, II
	Inland waterway transport ADNR	
	Class: UN Number: Packaging group: Label:	3 flammable liquids 1247 II 3
	Declaration of the good:	3 UN 1247 METHYL METHACRYLATE, MONOMER, STABILIZED, 3, II
	Shipment by sea IMDG/GGVSee	3
	Class: UN Number: EmS:	3 flammable liquids 1247 F-E, S-D
	Marine pollutant: Packing group:	-
	Proper Shipping Name:	METHYL METHACRYLATE, MONOMER, STABILIZED
	Air transport ICA/IATA	3
	Class: UN Number:	3 flammable liquids 1247
	Packing group: Proper Shipping Name:	IZ47 II METHYL METHACRYLATE, MONOMER, STABILIZED
14.5	DOT	UN 1247 METHYL METHACRYLATE, MONOMER, STABILIZED

reviewed on: 01.08.2009



Page: 6 / 6

15.	Regulations:		
	Labelling in accordance to EC directive GefStoffV:	requires labelling	
	Hazardous component for labelling: Hazardous symbols: Risk phrases (R-phrases)	contains methyl methacrylate F Highly flammable Xi Irritant 11 Highly flammable	
		 37/38 Irritating to respiratory system and skin 43 May cause sensitization by skin contact 	
	Safety Phrases (S-phrases)	 Avoid contact with skin Wear suitable gloves If swallowed, seek medical advice immediately and show container or label 	
15.	Regulations - continued		
	Occupational restrictions	 Note for juveniles Note for pregnant women and nursing mothers (EC Directive 92/85/EEC) 	
16.	Further information.		
	This product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is exceeded, the product may polymerize with heat evolution.		
	References	Relevant manuals and publications, Toxicological and ecotoxicological studies of other manufactures, SIAR, OECD-SIDS, RTK public files	

The above information describes exclusively the safety requirements of the product(s) and is based on our present-day knowledge. It does not represent a guarantee for the properties of the product(s) described in terms of the legal warranty regulations. Properties of the product are to be found in the respective product leaflet.