SAFETY DATA SHEET



Date Issued: 12/15/2006 MSDS No: 85-001.5 Date-Revised: 7/15/2013

Revision No: 5

PermaSeal®

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME: PermaSeal®

PRODUCT DESCRIPTION: Composite sealer and composite bonding agent

PRODUCT CODE/ PART #: PS/63010

MANUFACTURER

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (NORTH AMERICA) : (800) 424 - 9300

(INTERNATIONAL):+1(703) 527 - 3887

Ultradent Products, Inc. 505 W. 10200 S.

South Jordan, UT 84095

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS	EINECS	Classification	Wt.%
Bis GMA	1565-94-2	216-367-7	Xi; R36/37/38	60
Triethylene Glycol Dimethacrylate	109-16-0	203-652-6	Xi; R43	< 40
2-dimethylaminoethyl Methacrylate	2867-47-2	220-688-8	T, Xi; R22, R36/37/38, R43	2.6

(Full text of R-Phrases can be found under heading 16)

3. HAZARDS IDENTIFICATION

HAZARD DESIGNATION

"Xi" - Irritant

R43: May cause sensitization by skin contact.

R36/37/38: Irritating to eyes, respiratory system and skin.

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

SKIN: May cause skin irritation and sensitization.

INGESTION: May be irritating to mouth, throat and stomach.

INHALATION: May be harmful if inhaled.

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash clothing before reuse.

INGESTION: If swallowed, Do Not Induce Vomiting- Seek Medical Advice.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

SAFETY DATA SHEET



Date Issued: 12/15/2006 MSDS No: 85-001.5 Date-Revised: 7/15/2013 Revision No: 5

PermaSeal®

FIRE FIGHTING PROCEDURES: General: Evacuate all personnel; use protective equipment for fire-fighting. Use self-contained breathing apparatus when the product is involved in fire.

FIRE FIGHTING EQUIPMENT: Foam, dry chemical, carbon dioxide (CO₂).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Pick up wash liquid with additional absorbent and place in a disposable container.

LARGE SPILL: Collect in tightly closed containers.

7. HANDLING AND STORAGE

HANDLING: Use suitable protective equipment.

STORAGE: Store in a cool place in original container and protect from sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EOUIPMENT

EYES AND FACE: Wear eye protection

SKIN: S36/37: Wear suitable protective clothing and gloves.

RESPIRATORY: Good general ventilation should be sufficient to control airborne levels.S38: In case of insufficient ventilation, wear suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Acrylic **COLOR:** Yellow

10. STABILITY AND REACTIVITY

STABILITY: Stable when stored and handled under recommended conditions.

POLYMERIZATION: Stable when stored and handled under recommended conditions. **CONDITIONS TO AVOID:** Heat, flames, ignition sources, direct light, and incompatibles.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: Contact may cause eye irritation.

SKIN EFFECTS: May cause skin irritation and sensitization.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Do not flush to sewer.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in compliance with governmental regulation. (EC 1975L0442-20/11/2003)

SAFETY DATA SHEET



Date Issued: 12/15/2006 MSDS No: 85-001.5 Date-Revised: 7/15/2013

Revision No: 5

PermaSeal®

14. TRANSPORT INFORMATION

ROAD AND RAIL (ADR/RID)

LABEL: Not classified

AIR (ICAO/IATA)

LABEL: Not classified VESSEL (IMO/IMDG) LABEL: Not classified

15. REGULATORY INFORMATION

EUROPEAN COMMUNITY

EEC LABEL SYMBOL AND CLASSIFICATION



"Xi" - Irritant

R43: May cause sensitization by skin contact.

R36/37/38: Irritating to eyes, respiratory system and skin.

16. OTHER INFORMATION

RELEVANT R-PHRASES: R36/37/38: Irritating to eyes, respiratory system and skin.

R43: May cause sensitization by skin contact.

R22: Harmful if swallowed.

PREPARED BY: Anu Kattoju

REVISION SUMMARY: This MSDS replaces the 11/16/2010 MSDS. Revised: **Section 1:** PREPARED BY, PRODUCT CODE/ PART #. **Section 2:** POTENTIAL HEALTH EFFECTS (INHALATION, INGESTION). **Section 8:** PERSONAL PROTECTIVE EQUIPMENT - RESPIRATORY. **Section 11:** EYE EFFECTS. SKIN EFFECTS.

MANUFACTURER DISCLAIMER: FOR DENTAL USE ONLY: Use as directed. The information and recommendations are taken from sources (raw material MSDS(s) and manufacturer's knowledge) believed to be accurate; however, the manufacturer makes no warranty with respect to the accuracy of the information or the suitability of the recommendation and assumes no liability to any user thereof. Each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.