Material Safety Data Sheet

according Directive 91/155 EEC

Important: Read this MSDS before handling and disposing of this product and pass this

information on to employees, customers and users of this product.

1. Identification of the substance/preparation and company

1.1. Product Name: ResiCem (Primer B)

1.2. Company:

Shofu Dental GmbH Am Brüll 17 40878 Ratingen

Phone No. +49 (0)2102/8664-0 Fax-N: +49 (0)2102/8664-64

info@shofu.de

1.3. Emergency Phone No.

+49 (0)2102/8664-20

2. Composition/information on ingredients

Compositions given are typical values, not specifications

2.1. Ingredients Einecs nc % weight Symbol risk-phrases CAS-No. 2-Hydroxy Ethyl Methacrylate = 40% XI irritant 868-77-9 Acetone $\leq 20\%$ F flammable 67-64-1

Acrylic adhesive monomer

Others

3. Hazard identification

3.1. For the user: Irritating to eyes and skin

Possible nausea on prolonged exposure

Inhalation may occur sore throat, cough, confusion, headache

3.2. Environmental hazard: and/or dizziness

3.4 Hazard Designation: Flammable and irritant preparation. Symbols are F and Xi

4. First aid measures

4.1. Inhalation: Move to the open air

4.2. Skin contact: Wash immediately with soap and plenty of water

4.3. Eye contact: Flash with flowing water and consult physician

4.4. Ingestion: Consult physician

Revised Date: April 18, 2008 Issue No.: 1 Page 1/4

Material Safety DATA Sheet according Directive 91/155 EEC

5.	Fire-fighting measures							
J.	File-lighting measures							
5.1.	Extinguisher method:	foam, CO ₂ , dry chemical, water						
5.2.	Not useful method:							
5.3.	Special Exposure Hazards Arising:	Easily flammable liquid in room temperature						
5.4.	Special equipment for fire-fighting:	Irritation gases and fumes may emit Wear fire protective cloth and self-contained breathing apparatus if necessary						
6.	Accidental release measures							
6.1.	Personal precautions:	Avoid eye and skin contact -see section 8- Do not inhale vapor						
6.2.	Environmental precautions:	Dispose according to local, state and federal regulations						
6.3.	Methods for cleaning up	Wipe up and discard in a suitable container (leak-proof and gastight)						
7.	Handling and storage							
7.1.	Handling: Handle in a well ventilated place, keep away from naked flames, sparks and sources of heat, do not smoke. Wear protective gloves, safty spectaches or face shield							
7.1.1.	Precautions for safe handling:							
7.2.	Storage:	Store in a cool and dark fire proof area with container tightly closed. Separate from strong oxidants						
7.2.1.	Precautions for storage rooms:	Keep refrigerated when not in use						
7.2.2.	Storage of incompatible materials:							
7.2.3.	Special storage conditions:	Do not expose to sunlight or heat No smoking area						

Revised Date: April 18, 2008 Issue No.: 1 Page 2/4

Material Safety DATA Sheet

according Directive 91/155 EEC

8. Exposure controls/personal protection

8.1. Exposure controls:

8.1.1. ACGIH TLV Acetone[Cas No. 67–64–1] 1780 mg/m3

2HEMA [Cas no.868-77-9] None assigned

8.2. Respiratory protection: Not required (use protective gas mask for organic gases, if

necessarv

8.3. Hand protection: Protective gloves (latex or rubber)

8.4. Eye protection: Safety goggles (may be required)

8.5. Skin protection: not required (general working clothes)

9. Physical and chemical properties:

9.1. Appearance Liquid **Colour** colorless **Odour**: sweet

9.2. PH:

9.3. Boiling point: N/D

9.4. Melting point N/A

9.5. Flash point -12°C (close)

9.6. Explosion limits: Lower: Upper:

9.7. Relative density: 1.1 (water =1)

9.8. Vapour density:

9.9. Solubility: soluble in all purport

9.10. Viscosity:

9.11. Others:

10. Stability and reactivity:

10.1. Conditions to avoid: Visible light on the liquid, keep away from source of ignition

(electric discharge and smoking etc.)

10.2. Materials to avoid: Strong oxidizing materials

10.3. Hazardous decomposition products: may occur peroxide

10.4.. Others:

Revised Date: April 18, 2008 Issue No.: 1 Page 3/4

Material Safety DATA Sheet according Directive 91/155 EEC

11.	Toxicological information:					
11.1.	Acute Toxicity:	2HEMA 2HEMA	L D 50 = L D 50 =	ORAL-RAT ORAL-MUS	5050 mg/kg 3275 mg/kg	
11.1.1. 11.1.2. 11.1.3.	Ingestion: Inhalation: Skin contact:		Of the Vapour may cause headache, dizziness and vomiting			
11.1.4.	Eye contact:		Repeated contact to the mucous membrane of eyes, nose and throat cause inflammation			
11.2.	Chronic effects:					
11.2.1. 11.2.2. 11.2.3. 11.2.4. 11.2.5.						
12.	Ecological information:					
	Don't discard into the drain					
13.	Disposal considerations:					
13.1.	Material:		Disposal in a local regulati	accordance with fe ons	deral, state and	
13.2.	Packaging:					
14.	Transport information:					
			UN hazard C Pack group I	Class 3 II EN 1090 (as Acet	one)	
15.	Regulatory information:					
16.	Other information:					
			of product exclusively by dental specialists to instructions for use			
		N/D: No	data	N/A	: Not applicable	

Revised Date: April 18, 2008 Issue No.: 1 Page 4/4

Material Safety Data Sheet

according Directive 91/155 EEC

Some of the information presented and conclusions drawn herein are from sources other than direct test-data on the product itself.

The contents and format of this MSDS are in accordance with EEC Commission Directive 91/155 /EEC.

Disclaimer of Liability

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness.

The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge.

For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Revised Date: April 18, 2008 Issue No.: 1 Page 5/4