

Safety Data Sheet according to Regulation (EC) No 1907/2006

B. Braun Melsungen AG

Revision date: 15.03.2013

Revision No: 1,10

Softa-Man (DE)

00056-0003

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Softa-Man (DE)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hand disinfectant

1.3. Details of the supplier of the safety data sheet

B. Braun Melsungen AG

Carl-Braun-Straße 1

D-34212 Melsungen

B. Braun Medical AG

Seesatz 17

CH-6204 Sempach

Responsible Department

Zentrale Service-Bereiche/Logistik und Supply Chain

Telephone: +49 (0) 5661 / 71-4422

Emergency telephone :+49 (0) 6132 / 84463 (GBK Gefahrgut Buero GmbH, Ingelheim)

Responsible for the safety data sheet: sds@gbk-ingelheim.de

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant

R phrases:

Flammable.

Risk of serious damage to eyes.

Vapours may cause drowsiness and dizziness.

GHS classification

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye damage.

May cause drowsiness or dizziness.

2.2. Label elements

Danger symbols:

Xi - Irritant



Xi - Irritant

Hazardous components which must be listed on the label

Propan-1-ol

R phrases

10 Flammable.

Softa-Man (DE)

00056-0003

- 41 Risk of serious damage to eyes.
67 Vapours may cause drowsiness and dizziness.

S phrases

- 07 Keep container tightly closed.
16 Keep away from sources of ignition - No smoking.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
35 This material and its container must be disposed of in a safe way.
39 Wear eye/face protection.

2.2. Label elements (GHS classification)

Signal word:

Danger

Pictograms:

GHS02-GHS05-GHS07



Hazardous components which must be listed on the label

Propan-1-ol

Hazard statements

- H225 Highly flammable liquid and vapour.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe vapour.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P313 Get medical advice/attention.

Additional advice on labelling

Applies for those countries where this product is classified as medicinal product; as ready for use medicinal product, this product is not subject to labelling obligation according to the CE directives in these countries.

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alcoholic solution

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
200-578-6	Ethanol	< 55 %
64-17-5	F - Highly flammable R11	
603-002-00-5	Flam. Liq. 2; H225	
01-2119457610-43		
200-746-9	Propan-1-ol	< 25 %
71-23-8	F - Highly flammable, Xi - Irritant R11-41-67	
603-003-00-0	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336	
01-2119486761-29		

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
If you feel unwell, seek medical advice.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Drink plenty of water.
Do not induce vomiting.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye damage.
May cause drowsiness or dizziness.
Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
Carbon monoxide and carbon dioxide.

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation.

When using, do not eat, drink or smoke.

Avoid contact with eyes.

Advice on protection against fire and explosion

Keep product and empty container away from heat and sources of ignition.

Do not smoke - volatile.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Advice on storage compatibility

Incompatible with:

Oxidizing agents

Alkaline metals and earth alkaline metals.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hand disinfectant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
71-23-8	Propan-1-ol	200	500		TWA (8 h)	WEL
		250	625		STEL (15 min)	WEL

8.2. Exposure controls

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

When using, do not eat, drink or smoke.

Avoid contact with the eyes.

Remove and wash contaminated clothing before re-use.

Respiratory protection

No personal respiratory protective equipment normally required.

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

Eye protection

Safety goggles with side protection.

Eye wash bottle with pure water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
 Colour: Colourless
 Odour: Alcoholic

Test method

Changes in the physical state

Boiling point: 84 °C
 Flash point: 21 - 22 °C DIN 51755
 Lower explosion limits: 2,1 *)
 Upper explosion limits: *)
 Ignition temperature: 360 °C *)
 Vapour pressure: 59 hPa **) (at 20 °C)
 Density (at 20 °C): 0,86 g/cm³
 Water solubility: Miscible (at 20 °C)
 Solvent content: < 75 %

9.2. Other information

*) Propan-1-ol

**) Ethanol

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

Reactions with alkali metals.

Reactions with earth alkali metals.

10.4. Conditions to avoid

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents

Alkaline metals and alkaline earth metals.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No toxicological data available.

CAS No	Chemical name	Exposure routes	Method	Dose	Species	h
64-17-5	Ethanol					
	Acute oral toxicity		LD50	6200 mg/kg	Rat	
	Acute inhalation toxicity		LC50	95,6 mg/l	Rat	4

Irritation and corrosivity

Skin irritation: Not classified.

Eye irritation: Causes serious eye damage.

Sensitising effects

Not classified.

Severe effects after repeated or prolonged exposure

STOT - Single exposure: Category 3 [May cause drowsiness or dizziness.]

STOT - Repeated exposure: Not classified.

Aspiration hazard: Not classified.

Carcinogenic/mutagenic/toxic effects for reproduction

Carcinogenicity: Not classified.

Mutagenicity: Not classified.

Reproductive toxicity: Not classified.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Empirical data on effects on humans

Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

Swallowing renders reabsorption possible.

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

CAS No	Chemical name			
	Aquatic toxicity	Method	Dose	Species
64-17-5	Ethanol			h
	Acute fish toxicity	LC50	8140 mg/l	Golden orfe
	Acute crustacea toxicity	EC50	9268 - 14221 mg/l	Daphnia magna
				96
				48

12.2. Persistence and degradability

Ethanol / Propan-1-ol

Readily biodegradable (to OECD criteria)

12.3. Bioaccumulative potential

No data available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	Ethanol	- 0,31

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

When low concentrations are discharged correctly into adapted biological sewage treatment plants, interference with the degradation activity of activated sludge is not likely.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be disposed of as a solid waste or burned in a suitable installation subject to local regulations.

Where possible recycling is preferred to disposal.

Waste disposal number of waste from residues/unused products

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother liquors
Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number:** UN1987
- 14.2. UN proper shipping name:** ALCOHOLS, N.O.S. (Ethanol, Propan-1-ol)
- 14.3. Transport hazard class(es):** 3
- 14.4. Packing group:** II
- Hazard label: 3



Classification code: F1
Limited quantity: 1 L / 30 kg
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN1987
14.2. UN proper shipping name: ALCOHOLS, N.O.S. (Ethanol, Propan-1-ol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 1 L / 30 kg

Marine transport (IMDG)

14.1. UN number: UN1987
14.2. UN proper shipping name: ALCOHOLS, N.O.S. (ethanol, propan-1-ol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity: 1 L / 30 kg
EmS: F-E, S-D

Air transport (ICAO)

UN/ID number: UN1987
14.2. UN proper shipping name: ALCOHOLS, N.O.S. (ethanol, propan-1-ol, mixture)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity Passenger: Y341 / 1 L
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

Dangerous for the environment: no

Safety Data Sheet according to Regulation (EC) No 1907/2006

B. Braun Melsungen AG

Revision date: 15.03.2013

Revision No: 1,10

Softa-Man (DE)

00056-0003

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): < 75 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

- 10 Flammable.
- 11 Highly flammable.
- 41 Risk of serious damage to eyes.
- 67 Vapours may cause drowsiness and dizziness.

Full text of H statements referred to under Sections 2 and 3

- H225 Highly flammable liquid and vapour.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)