

Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 17-9416-3
 Version number:
 10.00

 Revision date:
 02/12/2013
 Supersedes date:
 28/11/2013

Transportation version number: 2.00 (06/08/2014)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VPS Tray Adhesive

Product identification numbers

70-2011-0649-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Dental Product

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

E Mail: tox.uk@mmm.com Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

This material is exempt from hazard classification according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive Indication of danger

Highly flammable; F; R11

Irritant; Xi; R36

R66

R67

Page: 1 of 11

For full text of R phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

Notes on labelling

Nota P applied to CASRN 64742-48-9.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Symbol(s)

None.

Contains:

No ingredients are assigned to the label.

Risk phrases None.

Safety phrases None.

Notes on labelling

This product is exempt from labelling per Directive 1999/45/EC as it is defined as a medical device according to Directive 93/42/EEC and is invasive or comes into contact with the human body.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Ethyl acetate	141-78-6	EINECS 205- 500-4	70 - 80	F:R11; Xi:R36; R66; R67 (EU)
				Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066 (CLP)
Siloxanes and silicones, di-Me	63148-62-9		20 - 30	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EINECS 265- 150-3	1 - 5	Xn:R65 - Nota 4,P (EU) Xi:R38; R67 (Self Classified)
				Asp. Tox. 1, H304 - Nota P (CLP) Skin Irrit. 2, H315; STOT SE 3, H336 (Self Classified)

Please see section 16 for the full text of any R phrases and H statements referred to in this section Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Page: 2 of 11

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids and solids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

Page: 3 of 11

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient CAS Nbr Agency Limit type Additional comments

Ethyl acetate 141-78-6 Health and TWA:200 ppm;STEL:400 ppm

Safety Comm.

(UK)

Naphtha (petroleum), 64742-48-9 Manufacturer TWA:100 ppm

hydrotreated heavy determined

Health and Safety Comm. (UK): UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Skin/hand protection

No chemical protective gloves are required. See Section 7.1 for additional information on skin protection.

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid.
Specific Physical Form: Viscous.

Appearance/Odour Orange liquid with characteristic organic solvent odour.

Odour threshold No data available. PH No data available.

Boiling point/boiling range 76.1 °C

Melting pointNo data available.Flammability (solid, gas)Not applicable.Explosive propertiesNot classifiedOxidising propertiesNot classified

Flash point -3.9 °C [Test Method: Closed Cup]

Autoignition temperature *No data available.*

Flammable Limits(LEL) 1.2 %
Flammable Limits(UEL) 11.5 %
Vapour pressure 17,465.2 Pa

Relative density > 1 [*Ref Std*:WATER=1]

Water solubility Nil

Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Evaporation rateNo data available.Vapour density> 1 [Ref Std: AIR=1]Decomposition temperatureNo data available.ViscosityNo data available.DensityNo data available.

9.2. Other information

Percent volatile *No data available.*

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

Heat.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance Condition

Formaldehyde Oxidation, heat or reaction Carbon monoxide. Oxidation, heat or reaction

Carbon dioxide.

Oxidation, heat or reaction

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eve contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause target organ effects after ingestion.

Target Organ Effects:

Single exposure may cause:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		Data not available or insufficient for classification;
			calculated ATE >5,000 mg/kg
Ethyl acetate	Dermal	Rabbit	LD50 > 18,000 mg/kg
Ethyl acetate	Inhalation-	Rat	LC50 70.5 mg/l
	Vapor (4		
	hours)		
Ethyl acetate	Ingestion	Rat	LD50 5,620 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Inhalation-		LC50 estimated to be 20 - 50 mg/l
	Vapor		
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Ethyl acetate	Rabbit	Minimal irritation

Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Naphtha (petroleum), hydrotreated heavy	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Ethyl acetate	Rabbit	Mild irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Naphtha (petroleum), hydrotreated heavy	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Ethyl acetate	Guinea	Not sensitizing
	pig	
Siloxanes and silicones, di-Me		Data not available or insufficient for classification
Naphtha (petroleum), hydrotreated heavy	Guinea	Not sensitizing
	pig	

Respiratory Sensitisation

Name	Species	Value
Ethyl acetate		Data not available or insufficient for classification
Siloxanes and silicones, di-Me		Data not available or insufficient for classification
Naphtha (petroleum), hydrotreated heavy		Data not available or insufficient for classification

Germ Cell Mutagenicity

Name	Route	Value
Ethyl acetate	In Vitro	Not mutagenic
Ethyl acetate	In vivo	Not mutagenic
Siloxanes and silicones, di-Me		Data not available or insufficient for classification
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Ethyl acetate			Data not available or insufficient for classification
Siloxanes and silicones, di-Me			Data not available or insufficient for classification
Naphtha (petroleum), hydrotreated heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Reproductive and/or Development	. Liicts				
Name	Route	Value	Species	Test result	Exposure Duration
Ethyl acetate		Data not available or insufficient for classification			
Siloxanes and silicones, di-Me		Data not available or insufficient for classification			
Naphtha (petroleum), hydrotreated heavy	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	Human	NOAEL Not available	

Page: 7 of 11

			classification			
Ethyl acetate	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	
		system depression	dizziness		available	
Siloxanes and silicones, di-			Data not available or insufficient			
Me			for classification			
Naphtha (petroleum),	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
hydrotreated heavy		system depression	dizziness	and	available	
				animal		
Naphtha (petroleum),	Inhalation	respiratory irritation	Some positive data exist, but the		NOAEL Not	
hydrotreated heavy			data are not sufficient for		available	
			classification			
Naphtha (petroleum),	Inhalation	nervous system	Some positive data exist, but the	Dog	NOAEL 6.5	4 hours
hydrotreated heavy			data are not sufficient for	_	mg/l	
			classification			

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Ethyl acetate	Inhalation	endocrine system liver nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.043 mg/l	90 days
Ethyl acetate	Inhalation	hematopoietic system			LOAEL 16 mg/l	40 days
Ethyl acetate	Ingestion	hematopoietic system liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3,600 mg/kg/day	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrotreated heavy	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days

Aspiration Hazard

Name	Value				
Ethyl acetate	Not an aspiration hazard				
Siloxanes and silicones, di-Me	Not an aspiration hazard				
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard				

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Siloxanes and	63148-62-9		Data not			
silicones, di-			available or			
Me			insufficient for			
			classification			
Ethyl acetate	141-78-6	Fish	Experimental	96 hours	LC50	212.5 mg/l
Ethyl acetate	141-78-6	Crustacea	Experimental	48 hours	EC50	164 mg/l
Ethyl acetate	141-78-6	Green algae	Experimental	72 hours	EC50	2,500 mg/l
Ethyl acetate	141-78-6	Water flea	Experimental	21 days	NOEC	2.4 mg/l
Naphtha	64742-48-9		Data not			
(petroleum),			available or			
hydrotreated			insufficient for			
heavy			classification			

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Ethyl acetate	141-78-6	Experimental		Photolytic half-	20.0 days (t	Other methods
		Photolysis		life (in air)	1/2)	
Siloxanes and silicones, di- Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	10 % weight	OECD 301D - Closed bottle test
Ethyl acetate	141-78-6	Experimental Biodegradation	14 days	BOD	66 % weight	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Naphtha	64742-48-9	Data not	N/A	N/A	N/A	N/A
(petroleum),		available or				
hydrotreated		insufficient for				
heavy		classification				
Siloxanes and	63148-62-9	Data not	N/A	N/A	N/A	N/A
silicones, di-		available or				
Me		insufficient for				
		classification				
Ethyl acetate	141-78-6	Experimental		Log Kow	0.73	Other methods
		Bioaccumulati				
		on				

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

180106* Chemicals consisting of or containing dangerous substances.

SECTION 14: Transportation information

70-2011-0649-2

ADR/RID: DANGEROUS GOODS IN EXCEPTED QUANTITIES, CLASS 3, (--).

IMDG-CODE: UN1133, ADHESIVES, 3, IMDG-Code segregation code: NONE, Dangerous Goods in excepted quantities,

EMS: FE,SD.

ICAO/IATA: DANGEROUS GOODS IN EXCEPTED QUANTITIES OF CLASS 3,UN1133.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066 Repeated exposure may cause skin dryness or cracking. H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Page: 10 of 11

List of relevant R-phrases

R11	Highly flammable.
R36	Irritating to eyes.
R38	Irritating to skin.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Revision information:

Revision Changes:

Section 13: EU waste code (product as sold) information information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 8: Personal Protection - Eye information information was modified.

Section 8: Eye/face protection information information was added.

Section 2: Label remarks information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk

Page: 11 of 11