

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Print date: 08.05.2014

Product code: 1956-0600

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

die:master duo

Further trade names

1956-0800 die:master Set red

1956-0900 die:master Set blue

1956-1000 die:master Set gold/silver

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lacquer

1.3. Details of the supplier of the safety data sheet

Company name:	Renfert GmbH	
Street:	Untere Giesswiesen 2	
Place:	D-78247 Hilzingen	
Telephone:	+49 7731 8208-0	Telefax: +49 7731 8208-70
e-mail:	info@renfert.com	
Contact person:	Frau Andris	Telephone: +49 7731 8208-927
Internet:	www.renfert.com	

1.4. Emergency telephone number:

Vergiftungs-Zentrale Freiburg
+49 761 19 240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: F - Highly flammable, Xi - Irritant
R phrases:
Highly flammable.
Irritating to eyes.
Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

GHS classification

Hazard categories:
Flammable liquid: Flam. Liq. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazard Statements:
Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.

2.2. Label elements

Hazardous components which must be listed on the label

butanone; ethyl methyl ketone
n-butyl acetate

Signal word:	Danger
Pictograms:	GHS02-GHS07

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Print date: 08.05.2014

Product code: 1956-0600

Page 2 of 7

**Hazard statements**

- H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves and eye/face protection.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

- EUH066 Repeated exposure may cause skin dryness or cracking.

Additional advice on labelling

The R and S phrases can be omitted if the pack contains no more than 0,125 litres.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Lacquer

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
201-159-0	butanone; ethyl methyl ketone	< 80 %
78-93-3	F - Highly flammable, Xi - Irritant R11-36-66-67	
606-002-00-3	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
204-658-1	n-butyl acetate	10 - 25%
123-86-4	R10-66-67	
607-025-00-1	Flam. Liq. 3, STOT SE 3; H226 H336	

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Immediately remove any contaminated clothing, shoes or stockings.

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Print date: 08.05.2014

Product code: 1956-0600

Page 3 of 7

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO₂), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.

Avoid contact with skin and eyes.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.

Keep away from sources of ignition. - No smoking.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Print date: 08.05.2014

Product code: 1956-0600

Page 4 of 7

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

refer to chapter 7. No further action is necessary.

Protective and hygiene measures

Do not breathe vapour.
 Avoid contact with skin, eyes and clothes.
 Wash hands before breaks and after work.
 Keep away from food, drink and animal feeding stuffs.

Eye/face protection

Wear eye/face protection.

Hand protection

Tested protective gloves must be worn Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection

Respiratory protection necessary at: insufficient ventilation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: colourless
 Odour: characteristic

pH-Value:

Test method
not applicable

Changes in the physical state

Initial boiling point and boiling range: 79 °C

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Print date: 08.05.2014

Product code: 1956-0600

Page 5 of 7

Flash point: - 5 °C DIN 51755 (cc)

Explosive properties

not explosive.
Vapours can form explosive mixtures with air.

Lower explosion limits: 1,2 vol. %

Upper explosion limits: 11,5 vol. %

Ignition temperature: 370 °C

Density (at 20 °C): 0,78 - 0,88 g/cm³

Water solubility: Immiscible

Viscosity / dynamic: The product has not been tested.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
123-86-4	n-butyl acetate	oral	LD50	14000 mg/kg	Ratte	

Irritation and corrosivity

Irritant effect on the skin: Not an irritant.
Causes serious eye irritation.

Sensitising effects

not sensitising.

STOT-single exposure

May cause drowsiness or dizziness.

Severe effects after repeated or prolonged exposure

Repeated exposure may cause skin dryness or cracking.

Practical experience**Observations relevant to classification**

Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Print date: 08.05.2014

Product code: 1956-0600

Page 6 of 7

Other observations

Has de-greasing effect on the skin.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Further information

Do not allow to enter into surface water or drains.

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Send to a hazardous waste incinerator facility under observation of official regulations.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other dangerous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263

14.2. UN proper shipping name: FARBE

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Marine transport (IMDG)

14.1. UN number: UN 1263

14.2. UN proper shipping name: PAINT

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Marine pollutant: no

Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Print date: 08.05.2014

Product code: 1956-0600

Page 7 of 7

Air transport (ICAO)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	PAINT
14.3. Transport hazard class(es):	3
14.4. Packing group:	II

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC): 89,2 %

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

Additional information

M 017 Lösemittel (BGI 621)

M 004 Reizende Stoffe / Ätzende Stoffe (BGI 595)

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

10	Flammable.
11	Highly flammable.
36	Irritating to eyes.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

Full text of H statements referred to under Sections 2 and 3

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)